



Part Number: 83028

Hook-Up/Lead Wire UL AWM Style 1180, (1) 20 AWG (7x28) SPC, TFE, 300V, 200°C

Product Description

One 20 AWG stranded (7x28) silver plated copper conductor, TFE insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

Conductor				
AWG	Stranding	Material	1	lo. of Conductors
20	7x28	SCC - Silver-coated Cop	oper 1	
Condu	Conductor Count: 1			
Conductor Size:		20 AW	'G	

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	0.068 in	0.015 in

Outer Jacket Material



Electrical Characteristics

Shielding: Unshielded	
-----------------------	--

Current

Max. Recommended Current [A]
6.5 A

Voltage

Non-UL Voltage Rating	UL Voltage Rating
1000 V	300 V RMS

Temperature Range

Non-UL Temp Rating:	200°C
UL Temp Rating:	200°C

Mechanical Characteristics

Bulk Cable Weight:	6.90 lbs/1000ft

Standards

UL AWM Style:	1180
ISO/IEC Compliance:	Other Standards
Military Specification:	MIL-W-16878/5

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes

EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Ple	enum (Y/N):	No

Part Number

Variants

Item #	Color	Footnote
83028 010100	Black	
83028 0101000	Black	SW
83028 006100	Blue, Light	
83028 0061000	Blue, Light	SW
83028 005100	Green, Dark	
83028 0051000	Green, Dark	SW
83028 003100	Orange	
83028 0031000	Orange	SW
83028 002100	Red	
83028 0021000	Red	SW
83028 009100	White	
83028 0091000	White	SW

Footnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)
Footnote:	W - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 75'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.