


RED INDICATES ORIGINAL

DWG SIZE	DATA CONTAINED IN THIS DOCUMENT IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE AND SHALL NOT BE RELEASED TO THE PUBLIC IN ANY FORM OR BY ANY MEANS WITHOUT EXPRESS WRITTEN PERMISSION.				REV ECD		REVISIONS		105-0376	SH 1C
	H	12581	ADDED: -15, -16 & -17; SH 2 REDRAWN; SEE ECD	DWN	APPROVED	DATE:	1/25/83			


TABLE 1	
DASH NO	DESCRIPTION
-1	TERM (NO CHAIN)
-2	TERM WITH 2.5 BRASS CHAIN
-3	TERM WITH 2.5 NYLON CHAIN
-4	TERM WITH 3.0 BRASS CHAIN
-5	TERM WITH 3.0 NYLON CHAIN
-6	TERM WITH 6.0 BRASS CHAIN
-7	TERM WITH 6.0 NYLON CHAIN
-8	TERM WITH 4.0 BRASS CHAIN
-9	TERM WITH 4.0 NYLON CHAIN

TABLE 2			
DASH NO	"A" DIA	"B" DIA	"C" DIA
-02	.630	.750	1.068
-03	.505	.625	.941
-04	.439	.562	.878
-05	.380	.500	.816
-06	.317	.437	.753
-07	.281	.408	.722
-08	.510	.750	1.068
-09	.567	.687	1.003
-09B	.330	.450	.766


INCH		MM		INCH		MM		INCH		MM	
.005	0.13	.290	7.37	.418	10.64	.625	15.88	.941	23.90		
.010	0.25	.295	7.49	.437	11.10	.630	16.00	1.003	25.48		
.030	0.76	.300	7.62	.436	11.15	.687	17.45	1.066	27.08		
.032	0.81	.317	8.05	.450	11.43	.722	18.34	2.15	53.50		
.062	1.57	.325	8.28	.500	12.70	.750	19.05	3.0	76.20		
.140	3.55	.330	8.38	.505	12.83	.753	19.13	4.0	101.60		
.200	5.08	.355	9.02	.56	14.22	.766	19.46	4.5	114.30		
.25	6.35	.380	9.65	.562	14.27	.816	20.73	6.0	152.40		
.278	7.06	.388	9.85	.567	14.40	.827	21.01	7.0	177.80		
.281	7.14	.406	10.31	.610	15.48	.878	22.30	10.0	254.00		




-1 SHOWN
NO CHAIN, STAINLESS STEEL ROPE OR MOUNTING LUG




-2-△ THRU -11-△ SHOWN
STANDARD CHAIN & BASIC MOUNTING LUG



-12-△ THRU
-17-△ SHOWN
STAINLESS STEEL ROPE AND BASIC MOUNTING LUG



-2-△ -02 THRU
-11-△ -09B SHOWN
STANDARD CHAIN AND BULKHEAD JACK MOUNTING LUG



-12-△ -02 THRU
-17-△ -09B SHOWN
STAINLESS STEEL ROPE AND BULKHEAD JACK MOUNTING LUG


△ NOTE LENGTH FOR SST ROPE WITH MTG LUG OPTION IS NOT MEASURED TO CENTER OF BULKHEAD MTG LUG

5. EXAMPLE OF COMPLETE MODEL NO:
TNN1-2-△-02
BASIC MODEL NO: TNN1 (50 OHM)
UTNN1 (75 OHM)
CHAIN/ROPE MATL AND LENGTH (SEE TABLE 1)
BULKHEAD JACK MOUNTING LUG (OPTIONAL) WITH BRASS OR NYLON CHAIN AND STAINLESS STEEL ROPE (SEE TABLE 2)

4. TERMINATED MALE COAXIAL 50 & 75 OHM N TYPE PLUG WITH CHAIN & MOUNTING LUG OPTIONS

△ RESISTANCE VALUE IN OHMS (1/2W, 1%) SHOWN SHORTED TO CASE AND RESISTOR

2. FINISH: TFS-1A (NICKEL)
1. ALL DIM ARE IN INCHES



QTY	DESCRIPTION	PART NUMBER	ITEM
10, UNLESS SPECIFIED			
10 ± .005			
90°			
ANGLE			
DWN I DCK 9-30-88	MATERIAL	CODE IDENT	DRAWING NO.
CHK G&M 10-6-88		14949	105-0376
ENGR			REV
APPR			H
NEXT ASSY	SCALE 2:1	DATE 11-27-72	SHEET 1C